

Taming Hydra



Have you ever found yourself here?

```
# other params:
flags.DEFINE_integer( 'max_train_iteration', 0,
                    'Limit on the iterations of training (0: no limit).')
flags.DEFINE_integer( 'steps_per_checkpoint', 20,
                    'How many training steps to do per checkpoint.')
flags.DEFINE_string( 'steps_no_checkpoint', '20',
                    'How many training steps to do before any checkpoint.')
flags.DEFINE_boolean( 'predict', False,
                    'set for predicting test data using learned model in "ckpt_dir" directory')

flags.DEFINE_boolean( 'train_and_predict', True,
                    'set for training on train data and then predicting test data using learned model in "ckpt_dir" directory')
flags.DEFINE_string( 'train_and_predict_output', 'train_and_predict_output.txt',
                    'comma separated output file for hyper parameter tuning purposes.')
# flags.DEFINE_string( 'perplexity_output', 'perplexity_output.txt',
#                     'comma separated output file for hyper parameter tuning purposes.')
# flags.DEFINE_string( 'perplexity_prob_fn', 'softmax',
#                     'function used for converting logits to probs for perplexity. either "softmax", "min_max" or "sigmoid".')
```



```
flags.DEFINE_string( 'slurm_job_id', '0',
                    'job id (and task id in case of array) from slurm')
flags.DEFINE_boolean( 'test_per_eval', True, 'debugging flag. do not set!')
# use sgd instead of adam
flags.DEFINE_string( 'eval_method', 'loss', 'either "metric" or "loss"')
flags.DEFINE_integer( 'nonimproving_steps', 50, 'stop training after this many checkpoints have been seen without validation improvement.')
```



```
DEFINED_FLAGS = set()
for k, _ in FLAGS.__flags.items():
    if not k in NON_DEFINED_FLAGS:
        DEFINED_FLAGS.add(k)
```

[illegible]


Or often write...

```
if main_args.sim == "mms" or main_args.sim == "MultiModalSearchSim":
    sim_class = MultiModalSearchSim
elif main_args.sim == "mmr" or main_args.sim == "MultiModalRecSim":
    sim_class = MultiModalRecSim
elif main_args.sim == "sss" or main_args.sim == "SemiSyntheticSearchSim":
    sim_class = SemiSyntheticSearchSim
else:
    raise NotImplementedError("This simulator has not been implemented yet.")

if main_args.policy == "random":
    policy_class = RandomPolicy
elif main_args.policy == "oracle":
    policy_class = OraclePolicy
elif main_args.policy == "logged":
    policy_class = LoggedPolicy
elif main_args.policy == "plackettluce":
    policy_class = PlackettLuceLoggedPolicy
elif main_args.policy == "plackettluceoracle":
    policy_class = PlackettLuceNoisyOracle
else:
    raise NotImplementedError("This logging policy has not been implemented yet.")
```


What is config management?

```
python train.py \  
  --optimizer adamw \  
  --learning_rate 0.0003 \  
  --weight_decay 0.9 \  
  --model model_a \  
  --layers 5 \  
  --hidden_dim 100 \  
  --dropout 0.2 \  
  --activation gelu \  
  ...
```



config.yaml

```
optimizer: adamw  
learning_rate: 0.0003  
weight_decay: 0.9
```


model/model_a.yaml

```
layers: 5  
hidden_dim: 100  
activation: gelu  
dropout: 0.2
```

What is Hydra?

Open-source framework from Meta building on the YAML framework OmegaConf

- Composable, hierarchical config files
- Dependency injection
- Sweep parameters in parallel SLURM jobs
- Dynamic working directories
- Logging (not today)



We'll use the Hydra icon to link related tutorials / resources in this talk.

Configuration Management



Basic setup

```
pip install hydra-core
```

main.py


```
import hydra
from omegaconf import DictConfig, OmegaConf

@hydra.main(
    version_base="1.3",
    config_path="config/",
    config_name="config"
)
def main(config: DictConfig):
    print(OmegaConf.to_yaml(config))

if __name__ == "__main__":
    main()
```

Project

```
├── config/
│   └── config.yaml
└── main.py
```



Primitive types

config/config.yaml


```
experiment: "my_awesome_experiment" # Strings
learning_rate: 0.001 # Numbers
early_stopping: True # Booleans
layers: # Lists
  - 256
  - 128
  - 64
splits: # Dictionaries
  train: 60
  val: 20
  test: 20
random_state: ??? # Missing value
```



Interpolation

config/config.yaml

```
# Interpolate variables:  
out_dir: "results/${experiment}/${now:%Y-%m-%d} / "  
  
# Access environment variables:  
api_key: ${oc.env:API_KEY}  
  
# Resorts to default value if not set:  
data_dir: ${oc.env:DATA_DIR, "my/default/"}
```



Use cases: Reference variables across files, dynamic path generation, change configs based on laptop/cluster, avoid storing secrets, optional values, etc.

Accessing variables


main.py

```
print(config.learning_rate) # Attribute-style access  
# 0.001
```

```
print(config["layers"]) # Dictionary-style access  
# [256, 128, 64]
```

```
print(config.out_dir) # Assemble variables at runtime  
# results/my_awesome_experiment/2025-10-07/
```

```
print(config.api_key)  
# Error: Environment variable 'API_KEY' not found
```



Config groups

config.yaml

```
optimizer: adam  
learning_rate: 0.0003  
weight_decay: 0.9
```

model/model_a.yaml

```
name: model_a  
hidden_dim: 100  
activation: gelu  
dropout: 0.2
```


model/model_b.yaml

```
name: model_b  
hidden_dim: 512  
activation: elu
```

output

```
optimizer: adam  
learning_rate: 0.0003  
weight_decay: 0.9  
model:  
  name: model_a  
  hidden_dim: 100  
  activation: gelu  
  dropout: 0.2
```

```
python main.py +model=model_a
```



Use cases: Switch between datasets, models, simulators, ...



Defaults & packages

config.yaml

```
defaults:  
  - _self_  
  - model: model_a  
  - model@retriever: model_a  
  - model@reranker: model_b
```

```
model:  
  name: Model A  
retriever:  
  name: Model A  
reranker:  
  name: Model B
```

Project



Runs & overrides

config.yaml

```
defaults:  
  - _self_  
  - model: model_a  
  
learning_rate: 0.003
```

Run default


```
python main.py
```

Override a config value

```
python main.py learning_rate=0.01
```

Append a new config value

```
python main.py +data=msmarco
```



Dependency Injection



Instantiating Python objects from configs

config.yaml


```
defaults:  
  - _self_  
  - model: model_a
```

config/model/model_a.yaml

```
_target_: src.models.ModelA  
name: Model A  
layers: 3  
...
```

main.py

```
from hydra.utils import instantiate  
  
def main(config: DictConfig):  
    model = instantiate(config.model)  
    model(...)
```



Use cases: Init datasets, models, etc. with different arguments

Multiruns & Sweeps




Multirun

Sweep over all combinations of model & random state:

```
python main.py -m model=model_a,model_b random_state=1,2,3
```

```
[2025-10-04 11:34:45,436][HYDRA] Launching 6 jobs locally
[2025-10-04 11:34:45,436][HYDRA]      #0 : model=model_a random_state=1
[2025-10-04 11:34:45,479][HYDRA]      #1 : model=model_a random_state=2
[2025-10-04 11:34:45,524][HYDRA]      #2 : model=model_a random_state=3
[2025-10-04 11:34:45,567][HYDRA]      #3 : model=model_b random_state=1
[2025-10-04 11:34:45,609][HYDRA]      #4 : model=model_b random_state=2
[2025-10-04 11:34:45,655][HYDRA]      #5 : model=model_b random_state=3
```





Working directory management

By default, Hydra creates a new directory per run based on date/time but this can be changed.

Thus, a file saved with `df.to_csv("test.csv")` is not saved in your project but in the run directory.

Use `hydra.utils.get_original_cwd()` to access files in your project root or use absolute paths.

Lastly, Hydra stores the assembled config per job in the job's working directory under **.hydra/config.yaml**.



Sweeps

Hydra supports custom parameters to define parameter search ranges.

config/config.yaml

```
python main.py -m \  
    layers=range(3,6) \ # Integer/ Float ranges  
    model=glob(*) \ # List all configs in directory  
    lr=interval(0.00001,0.001) \ # Constrain param tuners
```


Sweepers


The built-in sweeper performs grid search.

Hydra supports a range of black-box & Bayesian optimizers:

- [Ax](#)
- [Nevergrad](#)
- [Optuna](#)

Typically require parameter ranges and tuning budget.

I prefer incremental tuning strategies over black box



Launchers



Parallel jobs on SLURM using Submitit


```
pip install hydra-submitit-launcher
```

Hydra can apply files on the root config level

config/launcher/slurm.yaml

```
# @package _global_
defaults:
  - override /hydra/launcher: submitit_slurm

hydra:
  launcher:
    mem_gb: 32 # RAM per job
    cpus_per_task: 16 # CPUs per job
    array_parallelism: 8 # Max parallel jobs
    timeout_min: 60 # Timeout
    partition: gpu
    gres: gpu:nvidia_rtx_a6000:1 # GPUs per job
```



Parallel jobs on SLURM using Submitit

```
python main.py -m model=gctr,rctr,dctr +launcher=slurm
```

```
[2025-10-03 15:11:25,368][HYDRA] Submitit 'slurm' sweep output dir : multirun/2025-10-03/15-11-24
[2025-10-03 15:11:25,369][HYDRA] #0 : model=gctr +launcher=slurm
[2025-10-03 15:11:25,372][HYDRA] #1 : model=rctr +launcher=slurm
[2025-10-03 15:11:25,376][HYDRA] #2 : model=dctr +launcher=slurm
```

JOBID	PARTITION	NAME	USER	ST	TIME	NODES	Nodelist(Reason)	
	268091_1	gpu	main	phager	R	0:01	1	ilps-cn118
	268091_2	gpu	main	phager	R	0:01	1	ilps-cn118
	268091_0	gpu	main	phager	R	0:02	1	ilps-cn118

Some useful Design Patterns




Reuse parameters across files

config/data/msmarco.yaml

```
_target_: src.data.MSMarco  
vocab_size: 30_522
```

config/model/mono-bert.yaml

```
_target_: src.models.MonoBERT  
vocab_size: ${data.vocab_size}
```




Hyperparameters based on data & model

config/config.yaml


```
defaults:
  - _self_
  - data: msmarco
  - model: splade
  - hyperparameter: "${data}_${model}"
```

Auto-select parameters in next sweep:

```
python main.py data=msmarco,trec_covid
```



Project



Different configs between environments / people

config/config.yaml

```
defaults:  
  - _self_  
  - optional: env
```


config/env.yaml

```
data_dir: /my/local/path  
logger:  
  wandb_project: my_project  
  wandb_entity: my_entity  
launcher: slurm
```



→ Add file to .gitignore before

Project



The Sharp Bits



Debugging

When starting out with Hydra, error messages can be confusing, especially those caused by **lazy loading** and **dependency injection**.

Make sure to enable full stacktraces:

```
export HYDRA_FULL_ERROR=1
```

And **print the assembled config** at the beginning of your code.

```
print(OmegaConf.to_yaml(config))
```

Being too modular

By decoupling code and params, Hydra can make your code more opaque:

```
train_data = instantiate(config.train_data)
val_data = instantiate(config.val_data)
model = instantiate(config.model)
trainer = instantiate(config.trainer)

trainer.train(model, train_data, val_data)
```

Instead of making everything modular and configurable, try to focus on what actually needs to be varied across your experiments.

Hydra structured configs allows to write your configs as data classes (and enables advanced type checking & validation).

Summary

- Use config managers to escape endless if-else chains and long shell scripts. And avoid writing your own config managers.
- Hydra allows modular and hierarchical parameter configuration and dependency injection.
- Hydra enables parameter sweeps and SLURM management.
- The functionality of Hydra can be overwhelming at times. Start small, don't try to learn everything all at once.

